



Present Status of ERL project - 3GeV ERL and XFEL-O-

ERL Project
KEK/IMSS

Hiroshi Kawata
ERL Project Office, KEK

Contents

- What is ERL?
- Accelerator development in cERL
- Milestone toward 3GeV-ERL
- Summary
- Possible collaboration to produce high intense positron source



ERL Collaboration Team



High Energy Accelerator Research Organization (KEK)

S. Adachi, M. Akemoto, T. Aoto, D. Arakawa, S. Asaoka, K. Endo, A. Enomoto, S. Fukuda, K. Furukawa, T. Furuya, K. Haga, K. Hara, K. Harada, T. Honda, Y. Honda, H. Honma, T. Honma, K. Hosoyama, M. Isawa, E. Kako, Y. Kamiya, H. Katagiri, H. Kawata, Y. Kobayashi, Y. Kojima, T. Kume, T. Matsumoto, H. Matsumura, S. Michizono, T. Mitsuhashi, T. Miura, T. Miyajima, H. Miyauchi, N. Nakamura, S. Nagahashi, H. Nakai, H. Nakajima, E. Nakamura, K. Nakanishi, K. Nakao, T. Nogami, S. Noguchi, S. Nozawa, T. Obina, S. Ohsawa, T. Ozaki, H. Sagehashi, H. Sakai, S. Sakanaka, H. Sasaki, S. Sasaki, Y. Sato, K. Satoh, M. Satoh, T. Shidara, K. Shinoe, M. Shimada, T. Shioya, T. Shishido, T. Takahashi, R. Takai, T. Takenaka, Y. Tanimoto, M. Tobiyama, K. Tsuchiya, T. Uchiyama, A. Ueda, K. Umemori, K. Watanabe, M. Yamamoto, Y. Yamamoto, S. Yamamoto, Y. Yano, M. Yoshida



Japan Atomic Energy Agency (JAEA)

R. Hajima, R. Nagai, N. Nishimori, M. Sawamura, T. Shizuma, S. Matsuba



Institute for Solid State Physics (ISSP), University of Tokyo

I. Ito, H. Kudoh, T. Shibuya, H. Takaki



UVSOR, Institute for Molecular Science

M. Katoh, M. Adachi



Hiroshima University

M. Kuriki, H. Iijima



Nagoya University

Y. Takeda, Xiuguang Jin, T. Nakanishi, M. Kuwahara, T. Ujihara, M. Okumi



National Institute of Advanced Industrial Science and Technology (AIST)

D. Yoshitomi, K. Torizuka



JASRI/SPring-8

H. Hanaki



Yamaguchi University


H. Kurisu

Introduce myself

- Accelerator physicist? -> **No!!**
- Material scientist based on X-ray scattering by means of synchrotron radiation
- Resonant scattering, Resonant magnetic scattering, Compton scattering and XMCD
- One paper with Prof. Hyodo and Prof. Nagashima
- “High-Resolution Compton Scattering Study of Li: A Sphericity of the Fermi Surface and Electron Correlation Effect” Phys. Rev. Lett., (1995) 2252
*By Y.Sakurai, Y.Tanaka, A.Bansil, S.Kaprzyk, A.T.Stewart,
Y.Nagashima, T.Hyodo, S.Nanao, H.Kawata and
N.Shiotani*

Photon Factory

PAST AND FUTURE



1978年 計画始動での会場写真




1990年12月 建設中のフォトファクトリービル



1982年4月 ミシラン社訪問式典



1983年7月 共同利用実験開始後のPF実験ホール



1982:
First X-ray beam


2012:
30th Years Anniversary

2013:
First beam
from cERL




3500 users/ year

800 proposals / year



Outline of the ERL

http://pfwww.kek.jp/erl_info/



Beam characteristics of ERL

(electron beam size and divergence)


3rd generation SR

Beam size (μm)



H: 298 (1 σ)
V: 6.6 (1 σ)


Beam divergence (μrad)



H: 12.7 (1 σ)
V: 3.5 (1 σ)

ERL

H: 7.1 (1 σ)
V: 7.1 (1 σ)



H: 2.3 (1 σ)
V: 2.3 (1 σ)

SASE-XFEL




H: 28 (1 σ)
V: 28 (1 σ)



H: 0.28 (1 σ)
V: 0.28 (1 σ)




Energy Recovery Linac Conceptual Design Report




High Energy Accelerator Research Organization (KEK)

http://pfwww.kek.jp/ERLoffice/ERL_IAC/ERL%20CDR_latest%20version.pdf



- Beam energy
 - Full energy: 3 GeV
 - Injection and dump :10 MeV
- Geometry
 - Linac length : 470 m
- Straight sections for ID's
 - 22 x 6 m short straight
 - 6 x 30 m long straight

Target: spectral brightness



Figures are cited from: R. Hettel, "Performance Metrics of Future Light Sources", FLS2010, SLAC, March 1, 2010.

Symposium, Workshop

“ERL Science workshop II”: April of 2011

“ERL Symposium 2011”: July of 2011

“ERL2011”:(Accelerator Tech.) Oct. of 2011

“IMSS Symposium 2011”: Dec. of 2011

“2nd ERL Symposium”: March of 2012

“ERL Symposium 2011”



“ERL Symposium 2012”



“ERL Science workshop II”:



ERL2011 (Accelerator Tech.)




IMSS Symposium 2011




Our Goal:

Characterizing Functional Materials in Action



Compact ERL (cERL)

- Demonstrating reliable operations of our ERL components (guns, SC-cavities, ...)
- Demonstrating generation and recirculation of ultra-low emittance beams at high currents
- 1st target : 1 mm·mrad for 10mA @ 35 MeV




Photocathode DC Gun #1 at JAEA


8-hour operation at 510 kV with a segmented ceramic insulator

R. Nagai et al., Rev. Sci. Instrum. **81** (2009) 033304

Scheduled to be installed in
the cERL beamline this winter



Courtesy: N. Nishimori




Recently, 10mA beam production has been completed!

SC Cavities for Injector (1)

Courtesy: E. Kako, K. Watanabe



2-cell cavity



Input couplers




SC Cavities for Main Linac (1)



9-cell Cavities




HOM Absorber



Cryomodule design



Input coupler



Cryomodule design (side view)

Courtesy: K. Umemori

1.3 GHz CW RF Sources



300kW CW Klystron for injector SCC



30kW CW Klystron for injector SCC



Courtesy: T. Miura


30kW CW IOT for main SCC



20kW CW IOT for buncher

Liquid-Helium Refrigerator

Overview of the system



Courtesy: H. Nakai



3000L liquefied helium storage vessel



2K cold box and end box



TCF200 helium liquefier/refrigerator

Magnet/Vacuum/Monitor


Courtesy: K. Harada, Y. Tanimoto, T. Honda, T. Obina, R. Takai




Bending magnet



Quadrupole magnet



Zero-gap Flange



Stripline BPM
with glass-type feedthrough




Screen monitor




Slit for emittance
measurement

Construction schedule of the Compact ERL



3GeV-ERL construction schedule plan



Summary


- 3 GeV ERL covers wide range of user's demands such as coherent soft and hard X-rays, ultra-fast science using light pulses of $\Delta t=100$ fsec.
- ERL promises the further revolution of light source such as XFEL-O and EEHG.
- The cERL will start the operation from the end of FY2012.
- In order to progress the 3GeV ERL + XFEL-O project, we have organized several science workshops and symposia, and also start to accomplish the CDR
- After the operation of cERL , checking the performance of the accelerator components, we will finalize the design of 3GeV ERL at the level of TDR.

Collaboration Item with slow positron community

- *cERL and/or 3GeV-ERL have a potential to be a ultra-high intense positron source at the beam dump*
 - Present facility: 55MeV, 11 micro A → 600W at 50 Hz
(220 nC /bunch) → 10^6 e+/bunch
 - ERL: 5-10MeV, 10-100mA → 50-1000kW at 1.3 GHz
(7.7-77pC/bunch) → 10^{2-3} e+/bunch
- Coincidence measurement??

Outline of the ERL

http://pfwww.kek.jp/erl_info/



High brilliant
electron gun

Beam Dump
(10MeV x 100mA = 1MW)

Super conducting cavity for
Acceleration and deceleration